

# Eco Solvent Printer

1.8m i3200 Printhead

1.8米 爱普生 i3200 户内外写真机

1/2 Printheads 1/2 头可选

4/8 Color 4/8色写真

Variable Dot 可变墨滴

3-Stage Heater 三段加热



## ● Features



### Epson PrecisionCore Printheads

Equipped with Epson i3200 printhead, powered by Epson PrecisionCore technology. Born for fast speed and long-term running.



### Heating And Drying System

Front and middle and rear heating system and front drying fan are standard equipped to help dry the printed material fast.




### Anti-Collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.



### Branded Parts

Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Icus drag chain, Italian Megadyne belt.



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes.

- ★ New look has heavier, larger structure, and wider printing platform
- ★ Aluminous carriage girder ensures high accuracy of carriage movement
- ★ Dual feeding bar for loading heavy media
- ★ Optional infrared heater for drying prints quickly
- ★ Integrated temperature controller



## ● Specification

Model No.		SJ-740S	SJ-740i	SJ-740X
Printhead		2 × Epson i3200-E	1 × Epson i3200-E	1 × Epson i3200-U1HD
Resolution		2400dpi max	2400dpi max	2400dpi max
Ink Color		CMYK	CMYK	CMYK, Lc, Lm, Lk, LLk
Media	Size	1.8 meter		
	Types	Flex Banner, Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc.		
Speed	Draft	42 m <sup>2</sup> /h	25 m <sup>2</sup> /h	7.2 m <sup>2</sup> /h
	Production	32 m <sup>2</sup> /h	19 m <sup>2</sup> /h	4.5 m <sup>2</sup> /h
	Quality	24 m <sup>2</sup> /h	14 m <sup>2</sup> /h	2.5 m <sup>2</sup> /h
Ink Type		Eco Solvent Ink		
Ink Droplet		1.5-21pl variable		
Cleaning		Automatic Cleaning, Anti-Clogging Flash Function & Capping System		
Feed & take up		Automatic Media Feeding (Standard) & Take up System (Optional)		
Environment		Temperature: 20-28°C, Humidity: 40%-60%		
Rip Software		Maintop (Standard)/ FlexiPRINT (Optional)		
Interface		USB 3.0		
Power		AC 110/ 220V, 50/ 60Hz, 1200W		
Size & Weight	Machine	L3130 × W710 × H1380 mm / 280 KG		
	Packing	L3210 × W1000 × H740 mm / 400 KG		

Specifications are subject to change without notice.