

UV Roll To Roll Printer

Epson/Ricoh/Konica Printheads

Variable Dot

4/5/6/8 Colors

White & Varnish

INDUSTRIAL GRADE

SINOCOLOR




Features




Different Printheads Available

Epson i3200-U, Ricoh GEN5 & GEN6, Konica KM1024i-13pl printheads available. Meet the demands of different clients.




Material Tension System

Tension media feeding system is standard equipped to guarantee the high accuracy of material stepping.



Negative Pressure System

Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.



Dual Guide Rail

Dual guide rail configuration, guarantee the stability of long time running.



Anti-Collision System

Printer will automatically stop when the carriage hit any unexpected object during working, and support continuing printing from the interruption part, reduce the material waste.

- ★ Well-designed tension type material feeding and take-up system. Ensure the high accuracy of material stepping.
- ★ Mature time-set stirring system for white ink, effectively decrease the problems caused by white ink precipitation.
- ★ Elegant and sleek appearance design, not only an advanced printing equipment, but also a decoration for the company.



Specification

Model No.	UR-3200S	UR-3200R	UR-3200Rs	UR-3200K	
Printing Head	3/4 × Epson i3200-U	3/4 × Ricoh GEN5	3/4 × Ricoh GEN6	4/8 × Konica KM1024i-13pl	
Resolution	2400 dpi MAX	1200 dpi MAX	1200 dpi MAX	1440 dpi MAX	
Media	Width	3200 mm MAX			
	Type	Canvas, Leather, PET Film, Reflective Film, Soft Ceiling Film Etc.			
Ink	Type	UV Ink			
	Color	CMYK / CMYK+W / CMYK+W+V (Fluorescent Color and Gold Foil Varnish Available)			
	Curing	High Quality UV-LED Lamp			
Speed	Printing Mode	Color Mode			
	Draft	55 m ² /h (4 Heads)	30 m ² /h (4 Heads)	36 m ² /h (4 Heads)	80 m ² /h (8 Heads)
	Production	36 m ² /h (4 Heads)	15 m ² /h (4 Heads)	18 m ² /h (4 Heads)	55 m ² /h (8 Heads)
	Quality	25 m ² /h (4 Heads)	12 m ² /h (4 Heads)	14 m ² /h (4 Heads)	41 m ² /h (8 Heads)
Ink Supply System	Two Advanced Separate Negative Pressure Systems (One for Color and Varnish, One for White).				
Cleaning	Automatic Cleaning, Anti-Clogging Flash Function & Capping System				
Feed & TakeUp	Automatic Media Feeding (Standard) & Take up System (Optional)				
Rip Software	FlexiPRINT				
Connector	USB 3.0				
Power	AC 110/ 220V, 50/ 60Hz, 1800W				
Size	Machine	L5500 × W900 × H1630 mm			
	Packing	L5160 × W1100 × H1950 mm			
Weight	Machine	920 KG			
	Packing	1150 KG			

Specifications are subject to change without notice.